



Take your office productivity to a new level.

Kodak i100 Series Scanners



All the scanning performance and flexibility your busy office or department needs.

- Simplex (i150) and duplex (i160) models for colour, bitonal and greyscale imaging
- Perfect Page Scanning with iThresholding delivers sharp, clean images without rescanning
- Renowned SurePath paper handling that minimises jams
- Scans up to A3-size documents to handle your full workload
- 3-D ultrasonic multi-feed detection lets you scan with confidence
- Easy setup and operation
- Worldwide service and support for your peace of mind



KODAK Capture Software,
Lite



Features and Benefits

Perfect Page Scanning with iThresholding:

Advanced image processing from Kodak allows you to scan even poor-quality documents and get great images. Image cropping and straightening happen at full scanning speed. We've virtually eliminated the need to rescan or change settings so that you can be more productive, automatically.



Competitive scanner



Perfect Page Scanning with iThresholding, only from Kodak

Exclusive SurePath paper handling is designed for smooth paper transport and virtually jam-free operation.

Flexible feeding capability: Get through workloads faster by scanning documents up to A4 length (297 mm) in landscape mode. For more flexibility, the feeder handles documents up to 432 mm (A3 length) in portrait mode.

Five output options: Colour, bitonal, greyscale, simultaneous bitonal and greyscale and simultaneous bitonal and colour.

Electronic Colour Dropout: Suppress irrelevant red, green or blue backgrounds for efficient forms processing.

3-D multi-feed detection with ultrasonic technology lets you feed a wide variety of paper types and weights with confidence that you'll capture your images.

IEEE-1394 (FIREWIRE) interface allows for quick setup and speeds your images on their way. For your convenience, we also include the IEEE-1394 card and cable.

Small footprint and quiet operation: Both models scan large documents but are still small enough to fit easily on any desktop.

KODAK Capture Software, Lite installs in minutes and supports a range of scanning features for practically any office application. Easily upgradeable to the full version of Capture Software.

VRS Compatible for additional imaging options.

KODAK Service & Support: Our team of service experts is here for you around-the-clock, all over the world.

Specifications

Recommended Daily Volume	Up to 3,000 pages per day		
Throughput Speeds (Landscape, Letter Sized, Bitonal, Greyscale, Colour)	Resolution	i150 (simplex)	i160 (duplex)
	150 dpi	53 ppm	53 ppm/106 ipm
	200 dpi	40 ppm	40 ppm/80 ipm
	300 dpi	27 ppm	27 ppm/54 ipm
	Scanning with simultaneous output of bitonal and colour, or bitonal and greyscale, images		
	Resolution	i150 (simplex)	i160 (duplex)
	150 dpi	53 ppm/106 ipm	53 ppm/212 ipm
	200 dpi	40 ppm/80 ipm	40 ppm/160 ipm
	300 dpi	20 ppm/40 ipm	20 ppm/80 ipm
Scanning Technology	Single Tricolour Plus CCD (i150); Dual Tricolour Plus CCD (i160) Greyscale output bit depth is 256 levels (8-bit) Colour capture bit depth is 40-bit (10 bits per red, green, blue and black channels) Colour output bit depth is 24-bit		
Optical Resolution	300 dpi		
Illumination	Single 2500 hour+ Xenon lamps		
Output Resolution	75/100/150/200/240/300/400/600 dpi		
Maximum Document Size	297 mm x 432 mm		
Minimum Document Size	64 mm x 89 mm		
Paper Thickness and Weight	Onionskin to card stock		
Feeder	Automatic Document Feeder for continuous loading of up to 150 sheets of 60 g/m ² paper		
Multi-feed Detection	3-D multi-feed detection with ultrasonic technology		
Connectivity	IEEE-1394 (FIREWIRE) Interface (card and cable included), 6-pin connector		
Bundled Software	TWAIN and ISIS drivers; KODAK Capture Software, Lite		
Imaging Features (in the scanner)	Perfect Page Scanning with iThresholding, Autocrop, Aggressive Crop, Deskew, Electronic Colour Dropout, Halftone Removal, Noise Removal, VRS Compatible		
On-board compression	CCITT Group IV; JPEG or uncompressed output		
File Format Outputs	JPEG (for colour and greyscale images) TIFF (for bitonal images)		
Warranty	Standard: 12 months, on-site. Extended: 3 year, on-site option		
Electrical Requirements	100-240 V; 50-60Hz		
Environmental Factors	ENERGY STAR qualified scanners Mercury-free Xenon lamps Operating temperature: 15-30° C Operating humidity: 15% to 76% RH		
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <38.2 dB(A) Operating mode: <53.8 dB(A)		
PC Configuration	Minimum: PENTIUM III 1 GHz processor, 256 MB RAM Recommended: PENTIUM IV 2.4 GHz processor, 512 MB RAM		
Supported Operating Systems	WINDOWS 98SE, Me, 2000, XP		
Approvals and Product Certifications	UL 60950 2000-1, C-UL CAN/CSA-C22.2 No. 60950-1-03, TUV EN 60950-1:2001, CE Mark, 47 CFR Part 15 Subpart B (FCC) Class B, ICES-003 Issue 3 Class B, EN 55022:98 Class B, EN 61000-3-2 Powerline Harmonics, EN 61000-3-3 Flicker, EN 55024, AS/NZS CICPR 22 Class B (C-Tick Mark), CNS 13438 Class B, VCCI Class B, CISPR 22 Class B		
Consumables Available	Feed Module, Separator Module, Calibration Targets, Feeder Consumables Kit, Extra-Large Feeder Consumables Kit		
Accessories	Replaceable imaging guides White imaging background accessory		

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.

For more information visit: www.kodak.com/go/scanners



As an ENERGY STAR® Partner, Eastman Kodak Company has determined that these products meet ENERGY STAR® guidelines for energy efficiency.

We're here for you.

Kodak Service & Support

- Weight i150: 8.9 kg
i160: 10.4 kg
- Depth: 30.0 cm
- Width: 54.7 cm
- Height i150: 23.6 cm
i160: 36.5 cm

