

Kodak

i1300 Series Scanners



An awesome combination of performance and value, for all your departmental scanning needs.

Let's get right to it—the Kodak i1310 and i1320 Scanners deliver the highest level of capability and affordability of any product in their category. This is true breakout performance, with ease of use, versatility and image quality that sets a new benchmark.

Flexibility to meet wide-ranging needs

You can auto-feed virtually any document, from the size of a driver's license up to 863 mm (34 in.) long—at speeds up to 60 pages per minute. Scan both sides of documents in a single pass and output images in colour, bitonal or greyscale.

Our smart touch feature allows you to easily select the right scanning application for all kinds of jobs. At the touch of a button, scan documents to:

- file
- e-mail
- printers
- other desktop applications that support TIFF, JPEG, RTF, PDF and searchable PDF output

In addition, the i1300 Series Scanners have a unique tilt-and-scan feature that allows you to easily select the best scanning position for your job:

- Flat with trays extended for higher-volume batch scanning
- Fully upright with the input tray folded down for ad hoc and transaction feeding (your scanner can even be positioned up against a wall and still auto-feed documents)

And there's an optional tethered flatbed accessory (A4 size) for maximum convenience. In just seconds, attach the flatbed and scan your exception documents at up to 1200 dpi optical resolution. When you're finished, simply unplug and store the flatbed. It's that easy!

Enjoy sharp image quality

The i1310 and i1320 models feature 600 dpi optical resolution and enhanced Perfect Page image processing, a Kodak exclusive. This gives you images of exceptional quality—about as automatically as it gets. No need for rescans!

Finally, you can get high performance, ease of use and value at an affordable price point.

When you combine our image quality, ease of use and overall performance with the peace of mind that comes with Kodak Service & Support, the i1300 Series delivers truly awesome value.



Kodak i1300 Series Scanners

Recommended Daily Volume	Up to 3,000 pages per day
Throughput Speeds (portrait, letter size)	Bitonal/greyscale: Up to 60 ppm/120 ipm at 200 dpi Colour: Up to 30 ppm/60 ipm at 200 dpi
Scanning Technology	i1310: Single CCD; i1320: Dual CCD; Greyscale output bit depth is 256 levels (8-bit) Colour capture bit depth is 48 bits (16 x 3); Colour output bit depth is 24 bits (8 x 3)
Optical Resolution	600 dpi (i1310/i1320); 1200 dpi (A4 Flatbed Accessory)
Illumination	Dual fluorescent (cold cathode)
Imaging Backgrounds (customer replaceable)	Front white imaging background accessory included
Output Resolution	75, 100, 150, 200, 240, 300, 400, 600 and 1200 dpi
Maximum Document Size	215 mm x 863 mm
Minimum Document Size	50 mm x 63.5 mm
Paper Thickness and Weight	34-413 g/m ² paper; ID card thickness: up to 1.25 mm
Feeder	Up to 50 sheets of 75 g/m ² paper Handles small documents, such as ID cards, embossed cards and insurance cards
Multi-feed Detection	With ultrasonic technology
Connectivity	USB 2.0
Bundled Software	TWAIN and ISIS drivers; Kodak Capture Software, Lite ; Nuance ScanSoft OmniPage 14 and PaperPort 10 (or PaperPort Deluxe 9 Asian for China, Hong Kong, Japan, Korea and Taiwan)
Imaging Features (in the scanner)	Perfect Page Scanning; iThresholding; adaptive threshold processing; deskew; autocrop; relative cropping; aggressive cropping; electronic colour dropout; dual stream scanning; interactive colour, brightness and contrast adjustment; auto orientation; automatic colour detection; background colour smoothing
File Format Outputs	Single and multi-page TIFF, JPEG, RTF, PDF, searchable PDF
Warranty	One-year warranty, return to base
Accessories	Kodak A4 Flatbed Accessory with 1.8-meter cable; Optional flatbed black imaging background accessory
Electrical Requirements	100-240 V (International); 50-60 Hz
Power Consumption	i1310: Sleep mode: <6 Watts; Running: <35 Watts i1320: Sleep mode: <6 Watts; Running: <40 Watts
Environmental Factors	Energy Star qualified scanners Operating temperature: 15-35° C Operating humidity: 15% to 76% RH
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <30 dB(A) Operating mode: <58 dB(A)
Recommended PC Configuration	For documents up to 356 mm long at 400 dpi: Pentium IV , 3.2 GHz processor, 512 MB RAM For documents up to 660 mm long at 400 dpi: Pentium IV , 3.2 GHz processor, 1 GB RAM For longer documents/higher resolutions: Pentium IV , 3.2 GHz processor, 3 GB RAM
Supported Operating Systems	Windows XP SP2 (supports USB 2.0); Windows XP 64-bit edition Windows 2000 Professional (supports USB 2.0)
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950-1-03 (C-UL Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024 ITE Immunity, (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 (Class B), VCCI (Class B), CNS 13438 (Class B), CNS 14336, (BSMI Mark), UL 60950-1 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark
Consumables Available	Feed Module, Separation Module, Feed Rollers, Roller Cleaning Pads, Staticide Wipes
Dimensions	Weight: i1310: 5.2 kg, i1320: 5.5 kg Depth: 162 mm not including input tray and output tray Width: 330 mm Height: 246 mm not including input tray

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.